


GEOLOGIC CROSS-SECTION B - B'




PEAT - FORMER SWAMP & MARSH DEPOSITS PRIMARILY COMPOSED OF DECAYED PLANT MATERIAL AND SOME ORGANIC SILT, SAND, AND MUCK. TILL - FINE TO COARSE GRAVEL IN A DENSE MATRIX OF CLAY, SILT, AND SAND. ${
m SILT}$ — SILT WITH SOME CLAY AND TRACE AMOUNTS OF FINE SAND. DISCONTINUOUS LAYERS OF SAND AND GRAVEL MAY ALSO OCCUR. SAND — FINE TO COARSE SAND WITH VARIOUS AMOUNTS OF SILT, CLAY, AND GRAVEL, AND LENSES OF SILT AND CLAY. AREAS OF INTERMIXED SILTY SAND ARE DENOTED BY THE SYMBOL ———. SAND WITH GREATER THAN 20 PERCENT GRAVEL IS DENOTED BY GRAVEL SYMBOL % . GRAVEL - FINE TO COARSE GRAVEL WITH VARYING AMOUNTS OF SAND, SILT, CLAY <u>BEDROCK</u> — A MEDIUM TO FINE—GRAINED, THINLY LAMINATED, GREENISH—GRAY TO MEDIUM DARK GRAY CHLORITIC MUSCOVITE SCHIST WITH FINE TO MEDIUM GRAINED GRANOFELS COMPOSED PRIMARILY OF QUARTZ AND FELDSPAR. WELL/BORING ID


WELL SCREEN AND CORRESPONDING

GROUNDWATER ELEVATION

CORRESPONDING ELEVATION

 $rac{FILL}{L}$ - FILL CONSISTS OF MANUFACTURED OR CONSTRUCTION DEBRIS AND WASTE SLUDGE MIXED WITH NATURAL MATERIALS SUCH AS SILTY SAND, GRAVEL, OR TOPSOIL.





1. THE DEPTH AND THICKNESS OF THE SUBSURFACE STRATA WERE GENERALIZED FROM AND INTERPOLATED BETWEEN TEST BORINGS. THE STRATIFICATION LINES REPRESENT THE APPROXIMATE BOUNDARY BETWEEN SOIL TYPES AND THE TRANSITION MAY BE GRADUAL. INFORMATION ON SUBSURFACE CONDITIONS EXIST ONLY AT THE LOCATION OF THE TEST BORINGS AND IT IS POSSIBLE THAT THE SUBSURFACE CONDITIONS MAY VARY FROM THOSE INDICATED.

2. GROUNDWATER ELEVATIONS ARE ROUNDED TO THE NEAREST TENTH. GROUNDWATER ELEVATIONS ARE FROM ROUND SEVEN OF GROUNDWATER LEVEL MEASUREMENTS TAKEN ON 4/15/03, UNLESS OTHERWISE NOTED.

3. WELLS AT EACH CLUSTER WERE INSTALLED IN SEPARATE BOREHOLES. WELLS ARE INDICATED BY MULTIPLE SCREENS ON ONE AXIS FOR CLARITY. WIDTH OF WELL SCREENS ARE NOT TO SCALE.

4. MONITORING WELL DESCRIPTION: S=SHALLOW, M=INTERMEDIATE OVERBURDEN, D=DEEP OVERBURDEN, B=BEDROCK, DB=DEEP BEDROCK. MONITORING WELL DESIGNATION PC DENOTES POST CLOSURE WELL FOR OU1, MW DENOTES MONITORING WELL INSTALLED FOR OU2. SOIL BORING ADVANCED FOR ANOTHER OPERABLE UNITS IS DENOTED AS SB.

5. BASE PLAN COMPILED FROM THE FOLLOWING: DIVERSIFIED TECHNOLOGIES CORPORATION, NORTH HAVEN, CT; GEOD-PHOTOGRAMMETRIC SCIENCES SURVEY TECHNOLOGY, NEWFOUNDLAND, NJ; DELUCA-HOFFMAN ASSOCIATES, INC., S. PORTLAND, ME; CT-GIS; AND EPIC AERIAL PHOTOGRAPHY.

6. NOT FOR DESIGN.

7. ALL LOCATIONS TO BE CONSIDERED APPROXIMATE.

DRAWN BY: D.W. MACDOUGALL		OLOGIC CROSS-			
PREPARED BY: J. LAMBERT	_ RAY	'MARK — 0U2 -	 GROUNDWATER 	- 1	
CHECKED BY: M.HEALEY	REMEDIAL INVESTIGATION				
	STRATFORD, CONNECTICUT				
	SOURCE:			::	
	REFER TO NOTE 5				
2002 V (2000) - 2002 VIII VIII	SCALE: AS SHOWN	DATE: NOVEMBER	PROJ. NO: 8 5, 2004 N4236		
PROJECT MANAGER: H.M. FORD	DRAWING NO:		CFILE NAME:	REV:	
PROGRAM MANAGER: G.D. GARDNER			WG\4236\0600\B-B'.DWG	0	



55 JONSPIN ROAD WILMINGTON, MASSACHUSETTS 01887 (978)658 - 7899

GEOLOGIC CROSS-SECTION C - C'

NORTHWEST

FILL - FILL CONSISTS OF MANUFACTURED OR CONSTRUCTION DEBRIS AND WASTE SLUDGE MIXED WITH NATURAL MATERIALS SUCH AS SILTY SAND, GRAVEL, OR TOPSOIL.

TILL - FINE TO COARSE GRAVEL IN A DENSE MATRIX OF CLAY, SILT, AND SAND.

SILT - SILT WITH SOME CLAY AND TRACE AMOUNTS OF FINE SAND. DISCONTINUOUS

GRAVEL - FINE TO COARSE GRAVEL WITH VARYING AMOUNTS OF SAND, SILT, CLAY

<u>BEDROCK</u> — A MEDIUM TO FINE—GRAINED, THINLY LAMINATED, GREENISH—GRAY TO MEDIUM DARK GRAY CHLORITIC MUSCOVITE SCHIST WITH FINE TO MEDIUM GRAINED GRANOFELS COMPOSED PRIMARILY OF QUARTZ AND FELDSPAR.

CLAY - CLAY INTERBEDDED WITH SILT AND SAND.

LAYERS OF SAND AND GRAVEL MAY ALSO OCCUR.

GRAVEL SYMBOL % .

WELL SCREEN AND CORRESPONDING

GROUNDWATER ELEVATION

END OF BORING WITH

CORRESPONDING ELEVATION

SAND

EOB AT

WELL/BORING ID

CONTRACT RESIDENTIAL FORMER RAYMARK RESIDENTIAL **FACILITY PROPERTIES** FILL FILL FILL FILL SAND SAND SAND SILT GRAPHIC SCALE HORIZONTAL 1. THE DEPTH AND THICKNESS OF THE SUBSURFACE STRATA WERE GENERALIZED FROM AND INTERPOLATED BETWEEN TEST BORINGS. THE STRATIFICATION LINES REPRESENT THE APPROXIMATE SAND — FINE TO COARSE SAND WITH VARIOUS AMOUNTS OF SILT, CLAY, AND GRAVEL, AND LENSES OF SILT AND CLAY. AREAS OF INTERMIXED SILTY SAND ARE DENOTED BY THE SYMBOL ——. SAND WITH GREATER THAN 20 PERCENT GRAVEL IS DENOTED BY BOUNDARY BETWEEN SOIL TYPES AND THE TRANSITION MAY BE GRADUAL. INFORMATION ON C - C'SUBSURFACE CONDITIONS EXIST ONLY AT THE LOCATION OF THE TEST BORINGS AND IT IS TITLE: MAP VIEW POSSIBLE THAT THE SUBSURFACE CONDITIONS MAY VARY FROM THOSE INDICATED. 2. GROUNDWATER ELEVATIONS ARE ROUNDED TO THE NEAREST TENTH. GROUNDWATER ELEVATIONS ARE FROM ROUND SEVEN OF GROUNDWATER LEVEL MEASUREMENTS TAKEN ON 4/15/03, UNLESS OTHERWISE NOTED. 3. WELLS AT EACH CLUSTER WERE INSTALLED IN SEPARATE BOREHOLES. WELLS ARE INDICATED BY MULTIPLE SCREENS ON ONE AXIS FOR CLARITY. WIDTH OF WELL SCREENS ARE NOT TO SCALE. 4. MONITORING WELL DESCRIPTION: S=SHALLOW, M=INTERMEDIATE OVERBURDEN, D=DEEP OVERBURDEN, B=BEDROCK, DB=DEEP BEDROCK. MONITORING WELL DESIGNATION PC DENOTES POST CLOSURE WELL FOR OU1, MW DENOTES MONITORING WELL INSTALLED FOR OU2, AND SB DENOTES SOIL BORING NOT COMPLETED AS A WELL. SOIL BORING ADVANCED FOR ANOTHER OPERABLE UNIT IS DENOTED AS SB. 5. BASE PLAN COMPILED FROM THE FOLLOWING: DIVERSIFIED TECHNOLOGIES CORPORATION, NORTH HAVEN, CT; GEOD-PHOTOGRAMMETRIC SCIENCES SURVEY TECHNOLOGY, NEWFOUNDLAND, NJ; DELUCA-HOFFMAN ASSOCIATES, INC., S. PORTLAND, ME; CT-GIS; AND EPIC AERIAL PHOTOGRAPHY. NOT FOR DESIGN. 7. ALL LOCATIONS TO BE CONSIDERED APPROXIMATE. DRAWN BY: D.W. MACDOUGALL GEOLOGIC CROSS-SECTION C-C' RAYMARK - OU2 - GROUNDWATER PREPARED BY: J. LAMBERT REMEDIAL INVESTIGATION CHECKED BY: M.HEALEY TETRA TECH NUS, INC. STRATFORD, CONNECTICUT SOURCE: REFER TO NOTE 5 55 JONSPIN ROAD WILMINGTON, MASSACHUSETTS 01887 AS SHOWN N4236 NOVEMBER 8, 2004 PROJECT MANAGER: H.M. FORD

SOUTHEAST

DRAWING NO:

FIGURE 3-5

DWG\4236\0900\C-C'.DWG

PROGRAM MANAGER: G.D. GARDNER

(978)658-7899

